



**MARCO DESIGNS, BUILDS, INSTALLS,
COMMISSIONS & SERVICES PORTABLE
CONVEYORS FOR THE READY MIX INDUSTRY**

MARCO is uniquely positioned to provide the Ready-Mix industry with a portable conveyor that optimizes both productivity and conveyor life. The **MARCO** Portable Model 521, is constructed of the components utilized in much larger solutions, but at a price and functionality targeted at the Ready-Mix market's most demanding requirements.

**O
V
E
R

70+

Y
E
A
R
S**



**MARCO STACKABLE MODEL 521 CONVEYORS READY
FOR DELIVERY AND PRODUCTIVITY**



MODEL 521 STACKER



FREE STANDING SPAN CAPABILITY

MODEL 521 STACKER

MODEL 521: STACKABLE CONVEYOR

Belt Width	Conveyor Length	Slope	TPH	Motor HP	Head Pulley With Bearing	Slope	TPH	Motor HP	Head Pulley With Bearing
36"	72'	14°-18°	500	20	18" Dia. 215HB	9°-13°	500	15	16" Dia. 215HB
36"	68'	14°-18°	500	20	18" Dia. 215HB	9°-13°	500	15	16" Dia. 215HB
36"	64'	14°-18°	500	20	18" Dia. 215HB	9°-13°	500	15	16" Dia. 215HB
36"	60'	14°-18°	500	20	18" Dia. 215HB	9°-13°	500	15	16" Dia. 215HB
36"	56'	14°-18°	500	20	18" Dia. 215HB	9°-13°	500	15	16" Dia. 215HB
36"	52'	14°-18°	500	20	18" Dia. 215HB	9°-13°	500	15	16" Dia. 215HB
36"	48'	14°-18°	500	15	16" Dia. 215HB	9°-13°	500	15	16" Dia. 215HB
36"	44'	14°-18°	500	15	16" Dia. 215HB	9°-13°	500	15	16" Dia. 215HB
36"	40'	14°-18°	500	15	16" Dia. 215HB	9°-13°	500	15	16" Dia. 215HB
30"	72'	14°-18°	400	15	16" Dia. 215HB	9°-13°	400	15	16" Dia. 215HB
30"	68'	14°-18°	400	20	18" Dia. 215HB	9°-13°	400	15	16" Dia. 215HB
30"	64'	14°-18°	400	15	18" Dia. 215HB	9°-13°	400	15	16" Dia. 215HB
30"	60'	14°-18°	400	15	18" Dia. 215HB	9°-13°	400	15	16" Dia. 215HB
30"	56'	14°-18°	400	15	16" Dia. 215HB	9°-13°	400	10	16" Dia. 215HB
30"	52'	14°-18°	400	15	16" Dia. 215HB	9°-13°	400	10	16" Dia. 207SB
30"	48'	14°-18°	400	15	16" Dia. 215HB	9°-13°	400	10	16" Dia. 207SB
30"	44'	14°-18°	400	15	16" Dia. 215HB	9°-13°	400	10	16" Dia. 207SB
30"	40'	14°-18°	400	15	16" Dia. 215HB	9°-13°	400	10	16" Dia. 207SB
24"	72'	14°-18°	300	15	16" Dia. 215HB	9°-13°	300	10	16" Dia. 207SB
24"	68'	14°-18°	300	15	16" Dia. 215HB	9°-13°	300	10	16" Dia. 207SB
24"	64'	14°-18°	300	15	16" Dia. 215HB	9°-13°	300	10	16" Dia. 207SB
24"	60'	14°-18°	300	15	16" Dia. 215HB	9°-13°	300	10	16" Dia. 215HB
24"	56'	14°-18°	300	10	16" Dia. 207SB	9°-13°	300	7.5	16" Dia. 207SB
24"	52'	14°-18°	300	10	16" Dia. 207SB	9°-13°	300	7.5	16" Dia. 207SB
24"	48'	14°-18°	300	10	16" Dia. 207SB	9°-13°	300	7.5	16" Dia. 207SB
24"	44'	14°-18°	300	10	16" Dia. 207SB	9°-13°	300	7.5	16" Dia. 207SB
24"	40'	14°-18°	300	10	16" Dia. 207SB	9°-13°	300	7.5	16" Dia. 207SB

NOTE: ALL MODEL 521 CONVEYORS ARE: 400 FPM, TAIL PULLEY OF 14" DIA. WITH 207SB

STANDARD FEATURES:

- Head Pulley with Vulcanized Lagging XT Hubs and Bushings
- Tail Pulley (Self Cleaning) with XT Hubs and Bushings
- Reducer - Class II
- Idlers - Sealed Bearing CEMA B5 Carrier and Return
- Conveyor Belt - 2 Ply (Spliced)
- MARCO Paint System (Gray, Green or White)

STANDARD FEATURES: (CONT)

- Motor - 1800 RPM T.E.F.C..230/460 Volt
- "Rock Box" Type Loading Hopper

OPTIONAL FEATURES:

- Confining Chute (No Head Guard Required).
- Conveyor Supports
- Idlers - Sealed CEMA C5 Carrier and Return
- Belt Wiper
- Conveyor Belt - 3 Ply (Spliced or Vulcanized)

Continental Manufacturing Company

2275 Cassens Court, Ste 105

St Louis Missouri 63026

Phone: (800) 777-5852 or (636) 680-2031

Fax (636) 680-2037

Email: info@MarcoSolutions.net

www.MarcoSolutions.net